

# PRODUCT DATA SHEET

# STARFLOOR CLICK 30 Planks

Type of flooring

ISO 10582

Compact Resilient Flooring

Class of use

ISO 10874



23



31

Class

## Description



ISO 24346  
(EN 428)

4,00 mm



ISO 24340  
(EN 429)

0,30 mm



ISO 24342  
(EN 427)

122 cm  
18,3 cm



ISO 23997  
(EN 430)

7,4 kg/m<sup>2</sup>



EN 660-2  
Abrasion group

T  
≤ 2,00 mm<sup>3</sup>



ISO 4918  
(EN 425)  
Castor wheel test

OK



EN ISO 717/2  
Impact sound  
absorption

3 dB



ISO 24343-1  
(EN 433)  
Static indentation

≤ 0,08 mm

## Optional Characteristics



ISO 105/B02  
Light fastness

≥ 6



EN 1815  
Static electrical  
propensity

≤ 2 kV



Fire Classification

EN 13501-1  
Report N° : **Bfl-s1**  
**RA13-0130**



ISO 23999  
(EN 434)  
Dimensional stability

≤ 2 mm  
< 0,10 %



Recyclable

OK



ISO 24342  
9 Planks/box  
2,009 m<sup>2</sup>



ISO 10456  
(EN 12524)  
Thermal resistance  
for underfloor heating

0,03 m<sup>2</sup> k/W



Slip resistance  
EN 13893  
DIN 51130

μ ≥ 0,30  
R10



Although the utmost care is taken, the data here given could be imprecise and liable to modifications of a technical nature. In its strive to improve its floor solutions, Tarkett reserves the right to modify their technical specifications, colours and materials at any moment and without prior notice.